

# GA-016 Dingo, version 15X N0 19 40 11 5

There are more versions of **GA-016 Dingo** available at [lival.com](http://lival.com)  
 All-new, seamless cylinder design, GA-016 Dingo with deep-cut aluminium reflector is the optimal solution for accent lighting.



Lightsource	LED
Article Number	15X N0 19 40 11 5
Family Name	GA-016 Dingo
Luminaire Type	Tracklight
Adapter Type	GA-016
Mounting Type	Track mounted
Light Source Product Name	Citizen CLU038-1206/930BBL
Control Gear	on/off, DALI, BLL, Casambi, PIR
Light Distribution	Spot
Wattage	35 W
Luminous Flux	2510 lm
Efficacy (lm/W)	72 lm/W
COB Flux	3360 lm
Color Temperature	3000K
Color Rendering Index	Ra 90
Color Of Housing	Silver
IP Rating	20
Lifetime	50 000h (L80 B10)
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K
Color Consistency	MacAdams 2 SDCM
Material	Powder painted die-cast aluminium
UGR	3.8

