GA-016 Dingo, version 15X NO 19 40 12 5

There are more versions of **GA-016 Dingo** available at <u>lival.com</u> All-new, seamless cylinder design, GA-016 Dingo with deep-cut aluminium reflector is the optimal solution for accent lighting.

	W	/	
	v	-	

Liebberre	LED		
Lightsource	LED		
Article Number	15X NO 19 40 12 5		
Family Name	GA-016 Dingo		
Luminaire Type	Tracklight		
Adapter Type	GA-016		
Mounting Type	Track mounted		
Light Source Product Name	Citizen CLU038-1206/930BBL		
Control Gear	on/off, DALI, BLL, Casambi, PIR		
Light Distribution	Flood		
Wattage	35 W		
Luminous Flux	2610 lm		
Efficacy (Im/W)	75 lm/W		
COB Flux	3360 lm		
Color Temperature	3000K		
Color Rendering Index	Ra 90		
Color Of Housing	Silver		
IP Rating	20		
Lifetime	50 000h (L80 B10)		
Light Source Options	CRI 80+ 2700K, 3000K, 4000K, 5000K CRI 90+ 2700K Below BBL, 3000K Below BBL, 3500K Below BBL, 4000K Brilliant vivid 3000K, 4000K, 5000K Meat 2000K, Bakery 2400K		
Color Consistency	MacAdams 2 SDCM		
Material	Powder painted die-cast aluminium		
UGR	4.5		





