

Názov 3 fázového lištového systému


GLOBAL Trac Pro

L1/L2/L3/N/PE • 16A/400V • IP20






The recommended fastening distance is 1000 mm.
NOTE: A load not heavier than 10 kg may hang on a power takeoff adapter, the pull strength being 100 N (1kp = 9.81N) and the maximum torque 2.5 Nm. (GA 69 5 kg/50 N).



L/mm	a/mm	b/mm	c/mm	d/mm
1000	250			
2000	250	1000		
3000	250		1000	1000
4000	250		1500	1000




Lišty

GLOBAL Trac Pro tracks


Farby: – 1 šedá (AW 202JR), –2 čierna (RAL 9005), –3 biela (RAL 9010).

XTS 4100–4400



Type	EAN code	Dimensions in mm/ track length	Surface treatment/colour/ material	PCS/ Package
XTS 4100–1	64100 **14 507 01**–5	1000	Grey	4/240
XTS 4100–2	64100 **14 506 01**–8	1000	Black	4/240
XTS 4100–3	64100 **14 507 06**–0	1000	White	4/240
XTS 4200–1	64100 **14 507 02**–2	2000	Grey	4/240
XTS 4200–2	64100 **14 506 02**–5	2000	Black	4/240
XTS 4200–3	64100 **14 507 07**–7	2000	White	4/240
XTS 4300–1	64100 **14 507 03**–9	3000	Grey	4/240
XTS 4300–2	64100 **14 506 03**–2	3000	Black	4/240
XTS 4300–3	64100 **14 507 08**–4	3000	White	4/240
XTS 4400–1	64100 **14 507 04**–6	4000	Grey	4/240
XTS 4400–2	64100 **14 506 04**–9	4000	Black	4/240
XTS 4400–3	64100 **14 507 09**–1	4000	White	4/240

XTSF 4100–4400




Type	EAN code	Dimensions in mm/ track length	Surface treatment/colour/ material	PCS/ Package
XTSF 4100–1	64100 **14 507 51**–0	1000	Grey	6/180
XTSF 4100–2	64100 **14 506 51**–3	1000	Black	6/180
XTSF 4100–3	64100 **14 507 56**–5	1000	White	6/180
XTSF 4200–1	64100 **14 507 52**–7	2000	Grey	6/180
XTSF 4200–2	64100 **14 506 52**–0	2000	Black	6/180
XTSF 4200–3	64100 **14 507 57**–2	2000	White	6/180
XTSF 4300–1	64100 **14 507 53**–4	3000	Grey	6/180
XTSF 4300–2	64100 **14 506 53**–7	3000	Black	6/180
XTSF 4300–3	64100 **14 507 58**–9	3000	White	6/180
XTSF 4400–1	64100 **14 507 54**–1	4000	Grey	6/180
XTSF 4400–2	64100 **14 506 54**–4	4000	Black	6/180
XTSF 4400–3	64100 **14 507 59**–6	4000	White	6/180


GLOBAL Trac Pro accessories

Power supply option in all connectors except XTS 21, XTS 23 and XTS 24. All materials used are halogen free and VO-self-extinguishing. Available colours: –1 grey (RAL 7040), –2 black (RAL 9005), –3 white (RAL 9010).

End feed XTS 11



XTS 12




Type	EAN code	Polarity ridge	Surface treatment/colour/ material	PCS/ Package
XTS 11–1	64100 **14 507 15**–2		Grey	10/100
XTS 11–2	64100 **14 506 11**–7		Black	10/100
XTS 11–3	64100 **14 507 11**–4		White	10/100
XTS 12–1	64100 **14 507 16**–9		Grey	10/100
XTS 12–2	64100 **14 506 12**–4		Black	10/100
XTS 12–3	64100 **14 507 12**–1		White	10/100

GLOBAL Trac Pro accessories


Power supply option in all connectors except XTS 21, XTS 23 and XTS 24.
Available colours: –1 grey (RAL 7040), –2 black (RAL 9005), –3 white (RAL 9010).

Middle feed
XTS 14




Type	EAN code	Polarity ridge	Surface treatment/colour/ material	PCS/ Package
XTS 14–1	64100 **14 507 17**–6		Grey	5/50
XTS 14–2	64100 **14 506 14**–8		Black	5/50
XTS 14–3	64100 **14 507 14**–5		White	5/50

Straight connector
XTS 21




XTS 21–1	64100 **14 507 18**–3		Grey	10/100
XTS 21–2	64100 **14 506 21**–6		Black	10/100
XTS 21–3	64100 **14 507 21**–3		White	10/100

Flexible corner connector
XTS 23




XTS 23–1	64100 **14 507 20**–6		Grey	5/25
XTS 23–2	64100 **14 506 23**–0		Black	5/25
XTS 23–3	64100 **14 507 23**–7		White	5/25

Adjustable corner connector
XTS 24




XTS 24–1	64100 **14 507 19**–0		Grey	5/25
XTS 24–2	64100 **14 506 24**–7		Black	5/25
XTS 24–3	64100 **14 507 24**–4		White	5/25





L–feed
XTS 34, 35



XTS 34–1	64100 **14 507 25**–1		Grey	5/25
XTS 34–2	64100 **14 506 34**–6		Black	5/25
XTS 34–3	64100 **14 507 34**–3		White	5/25
XTS 35–1	64100 **14 507 26**–8		Grey	5/25
XTS 35–2	64100 **14 506 35**–3		Black	5/25
XTS 35–3	64100 **14 507 35**–0		White	5/25


T–feed
XTS 36, 37, 39, 40



XTS 36–1	64100 **14 507 27**–5		Grey	5/25
XTS 36–2	64100 **14 506 36**–0		Black	5/25
XTS 36–3	64100 **14 507 36**–7		White	5/25
XTS 37–1	64100 **14 507 28**–2		Grey	5/25
XTS 37–2	64100 **14 506 37**–7		Black	5/25
XTS 37–3	64100 **14 507 37**–4		White	5/25
XTS 39–1	64100 **14 507 30**–5		Grey	5/25
XTS 39–2	64100 **14 506 39**–1		Black	5/25
XTS 39–3	64100 **14 507 39**–8		White	5/25
XTS 40–1	64100 **14 507 31**–2		Grey	5/25
XTS 40–2	64100 **14 506 40**–7		Black	5/25
XTS 40–3	64100 **14 507 40**–4		White	5/25

X–feed
XTS 38



XTS 38–1	64100 **14 507 29**–9		Grey	5/25
XTS 38–2	64100 **14 506 38**–4		Black	5/25
XTS 38–3	64100 **14 507 38**–1		White	5/25

End cap
XTS 41




XTS 41–1	64100 **14 507 32**–9		Grey	10/100
XTS 41–2	64100 **14 506 41**–4		Black	10/100
XTS 41–3	64100 **14 507 41**–1		White	10/100

GLOBAL Trac Pro other parts

Available colours: –1 grey (RAL 7040), –2 black (RAL 9005), –3 white (RAL 9010).

Hook base
XTAK 142, 144, 146




Type	EAN code		Surface treatment/colour/ material	PCS/ Package
XTAK 142–1	64100 **14 507 43**–5	For 2 mm wire/hook	Grey	50/250
XTAK 142–2	64100 **14 506 42**–1	For 2 mm wire/hook	Black	50/250
XTAK 142–3	64100 **14 507 42**–8	For 2 mm wire/hook	White	50/250
XTAK 144–1	64100 **14 507 45**–9	For M4 nut/rod	Grey	50/250
XTAK 144–2	64100 **14 506 44**–5	For M4 nut/rod	Black	50/250
XTAK 144–3	64100 **14 507 44**–2	For M4 nut/rod	White	50/250
XTAK 146–1	64100 **14 507 47**–3	For M6 nut/rod	Grey	50/250
XTAK 146–2	64100 **14 506 46**–9	For M6 nut/rod	Black	50/250
XTAK 146–3	64100 **14 507 46**–6	For M6 nut/rod	White	50/250

Hook
XTAK 11




XTAK 11–1	64100 **14 500 79**–5	Hook 2 mm	Steel	100/5000

Tool
XTSV 12




XTSV 12	64100 **14 500 99**–3	Bending tool for power wires	Blue	1/100

Cover plates
XTSF 10




XTSF 10–1	64100 **14 500 41**–2	Cover plate for XTS11–14	Grey	1/100
XTSF 10–2	64100 **14 506 61**–2	Cover plate for XTS11–14	Black	1/100
XTSF 10–3	64100 **14 507 61**–9	Cover plate for XTS11–14	White	1/100

XTSF 30




XTSF 30–1	64100 **14 506 42**–9	Cover plate for XTS34–40	Grey	1/100
XTSF 30–2	64100 **14 506 62**–9	Cover plate for XTS34–40	Black	1/100
XTSF 30–3	64100 **14 507 62**–6	Cover plate for XTS34–40	White	1/100

XTSF 40



XTSF 40–1	64100 **14 506 43**–6	Outlet/cover plate for feeds	Grey	1/100
XTSF 40–2	64100 **14 506 63**–6	Outlet/cover plate for feeds	Black	1/100
XTSF 40–3	64100 **14 507 63**–3	Outlet/cover plate for feeds	White	1/100

Cover strip
XTSP 11



XTSP 11–2	64100 **14 530 99**–0	Cover strip, 3000 mm	Black	10/100
XTSP 11–3	64100 **14 530 98**–3	Cover strip, 3000 mm	White	10/100

Use of L- and T-accessories

Red line indicates polarity ridge

